

# Towards Rational Design for FRP Reinforced Concrete in Fire

**Mark F. Green** and Hamzeh Hajiloo  
Queen's University, Kingston, Canada

Noureddine Bénichou and Mohamed Sultan  
National Research Council, Ottawa, Canada



Buildings need to be designed for fire safety

- FRP reinforced concrete buildings need design procedures for fire

US Bridges (1980 to 2012)


- 30 failures due to fire
  - 20 failures due to earthquake
- (Lee et. al. A study of US bridge failures)




Credit: Associated Press

An aerial view of the collapsed freeway overpass near downtown Oakland

The Concrete Convention and Exposition




# (1) Realistic Fire Intensity



The Concrete Convention  
and Exposition


After haniso.co.kr and Bisby and Stratford (2013)



## (3) Realistic Loads During Fire

The significance of realistic loads are discussed using the results of the latest fire tests on FRP RC slabs at NRC, Ottawa.

Full-scale slabs with **60** mm clear concrete cover:




Width	Thickness	Clear Cover	Span	$M_f$	$M_{Ser}$	$M_{cr}$	$M_r$
mm	mm	mm	m	kN-m	kN-m	kN-m	kN-m
1200	200	60	3.8	32.5	23.4	25.8	84

**The moment in fire was 45 kN.m (33 kip.ft)**


Overloaded by 90% with respect to service moment.

The Concrete Convention  
and Exposition

Live load deflection limit  $l_n/360 = 10.5 \text{ mm (0.4 in.)}$




Calculated Deflections




Measured Deflections

The Concrete Convention and Exposition

## Full-scale slabs with 60 mm clear concrete cover:



**Deflection vs time during fire test**




**Deflection vs furnace temperature**

NOTE: Deflections in the above curves are due to only fire plus the effect of load increase at the end of test.



Full-scale slabs with **40 mm** clear concrete cover:



Design of a FRP reinforced concrete slab


Width	Thickness	Clear Cover	Span	$M_f$	$M_{Ser}$	$M_{cr}$	$M_r$
mm	mm	mm	m	kN-m	kN-m	kN-m	kN-m
1200	200	40	3.8	32.5	23.4	26.3	92

**The moment in fire was 45 kN.m.**

Overloaded by 90% with respect to service moment.


The Concrete Convention  
and Exposition

Full-scale slabs with **40 mm** clear concrete cover:




**Deflection vs time during fire test**

## Temperatures reduce towards the end of slab



Closely placed thermocouples in anchor zone (200 mm)





Material tests conducted on bond strength of FRP reinforcements at elevated temperatures




The Concrete Convention and Exposition

## Some of pullout tests results:



The Concrete Convention  
and Exposition



Various types of failure in steady-state temperature tests

## Vulnerability of FRP reinforcing bars to bond loss:



All FRP bars were pulled out at one end of Slab-B.



Post-fire condition of FRP bar in cool zone

The Concrete Convention and Exposition

- All bars embedded in support
- First test 160 MPa (23 ksi) and 2600  $\mu\epsilon$
- Second test 200 MPa (30 ksi) and 3300  $\mu\epsilon$
- ACI 440 stress limits (GFRP)
  - $0.2 f_{fu} = 200$  to 340 MPa (30 to 50 ksi)
- CSA S806/S6 strain limits for crack control
  - 2000  $\mu\epsilon$



- Realistic fires include cooling phase
  - ❑ For short-term, focus on standard fire
  - ❑ Longer-term, Eurocode approach
- Thermal modelling
  - ❑ Reasonable approaches and information
  - ❑ *What about spalling?*
- Realistic loads for FRP reinforced
  - ❑ Strength does not govern design
  - ❑ *How to establish design loads?*
- Anchorage and stress levels
  - ❑ *How to design appropriate anchorage?*

- Natural Sciences and Engineering Research Council of Canada (NSERC)
- MITACS Canada
- Ministry of Transportation of Ontario (MTO)
- Pultrall Inc.
- BP Composites Ltd.



Thank you for your attention

