

EVALUATION OF ALTERNATIVE SOURCES OF SUPPLEMENTARY CEMENTITIOUS MATERIALS FOR CONCRETE MATERIALS

Sujata Subedi

Gabriel A. Arce

Marwa M. Hassan

Louisiana State University



Miladin Radovic

Oscar Huang

Texas A&M University



Zahid Hossain

Arkansas State University



March 27th, 2022

Presentation Outline

2


- Introduction
- Objectives
- Methodology
- Results
- Conclusions

INTRODUCTION

Fly Ash

4



- Fly ash (FA) from coal-burning power production is the most widely utilized SCM in the US
- Its use in concrete:
 - Enhances concrete durability and long-term mechanical properties
 - Reduces concrete carbon footprint
 - Improves workability, reduces bleeding, and enhances pumpability
 - Mitigate alkali-silica reactivity (ASR)
 - Specially, highly pozzolanic **Class F fly ash**



Fly Ash Availability

5

- FA has become common practice in the US
- FA demand in the US is expected to increase
- Coal-fired power generation is declining
- Finding high quality and economical FA is becoming increasingly challenging
 - In a recent AASHTO survey (including the participation of 46 State DOTs), **80% of respondents indicated issues with fly ash supply**



Reclaimed Fly Ash and Bottom Ash

6

- Large amounts of coal ashes are disposed in landfills due to:
 - ▣ Market disparities (e.g., excessive seasonal supply)
 - ▣ Logistical challenges (e.g., storage space constrains)
 - ▣ Failure to meet specification (i.e., ASTM C618)
- FA from landfills can be dried and processed to meet specifications
 - ▣ This FA is referred to as reclaimed FA (RFA)
- More than 1000 million tons of FA in landfills and impoundments in the US
- Reclaimed bottom ash also has potential to be used as SCMs when appropriately processed
 - ▣ Reclaimed ground bottom ash (GBA)



Washingtonville RFA landfill

Problem Statement

7

- FA availability is a significant issue affecting the concrete industry
- Unconventional coal ash products (i.e., RFA and GBA) are promising alternatives
 - RFA and GBA properties can vary significantly depending on the supplier and source
- There is a need to explore alternative SCM sources to broaden the portfolio of alternatives

OBJECTIVES

Objective

9

- Evaluate alternative sources of SCMs for the manufacture of concrete for transportation infrastructure in Region 6.
- SCMs evaluated included:
 - Reclaimed fly ash (RFA)
 - Reclaimed ground bottom ash (GBA)
 - Conventional Class F fly ash (FA) as control

METHODOLOGY



SCMs Characterization

SCMs Evaluated

12



Reclaimed Fly Ash
(Georgia)



Ground Bottom Ash
(Texas)



Class F Fly Ash
(Illinois)

Characterization

13


- Scanning Electron Microscopy (SEM)
- X-Ray Fluorescence (XRF)
- X-Ray Diffraction (XRD)
- Laser Scattering Particle Size Analysis
- Loss on Ignition (LOI)
- Moisture Content
- Strength Activity Index (SAI)
- Thermogravimetric Analysis (TGA)
 - $\text{Ca}(\text{OH})_2$ and SCM (at 3:1 mass ratio) in 0.5 M KOH solution (at 0.9 liquid-to-solid ratio)
 - Tested after 10 days at 50°C



SEM/ EDS



Strength Activity Index



Particle Size Analyzer



XRD

13



Concrete Testing

Materials

15


- Ordinary Portland Cement (OPC) Type I
- Limestone (SG of 2.68 & MAS of 19 mm)
- Silica sand (SG of 2.65 & MAS of 4.75 mm)
- SCMs
 - ▣ Class F Fly Ash (FA)
 - ▣ Reclaimed Fly Ash (RFA)
 - ▣ Reclaimed Ground Bottom Ash (GBA)
- High-Range Water Reducer (HRWR)
 - ▣ Polycarboxylate based



Cement



Limestone



Silica Sand



Fly Ash

Experimental Matrix

16

- Concrete mixtures incorporating SCMs (i.e., RFA, GBA, MK, and FA) at 10, 20, and 30% cement replacement (by mass) were evaluated
- A total of 13 concrete mixtures were produced
 - ▣ 12 mixtures incorporating SCMs in binary systems (RFA, GBA, and FA)
 - ▣ 1 control mixture without SCMs

Control Concrete Mixture

17

- Louisiana DOTD Type A1 Structural Concrete
 - $w/c=0.45$
 - Target $f'_c=4500$ psi (31 MPa)
 - Target slump= 4 inches
 - Target Air Content = 6%

Mixture Proportions						
ID	Cement (kg/m ³)	Coarse Aggregate (kg/m ³)	Fine Aggregate (kg/m ³)	Water (kg/m ³)	HRWR (L/m ³)	AEA (L/m ³)
CO	344.1	1058.2	743.7	154.2	0.42	0.36

Mixture Proportions

18

ID	Cement (kg/m ³)	SCM (kg/m ³)	SCM (%) ^a	Coarse Aggregate (kg/m ³)	Fine Aggregate (kg/m ³)	Water (kg/m ³)	HRWR (L/m ³)	AEA (L/m ³)
CO	344.1	0	0	1058.2	743.7	154.2	0.42	0.36
FA-10	309.7	34.4	10	1058.2	734.0	154.2	0.42	0.36
RFA-10	309.7	34.4	10	1058.2	738.5	154.2	0.42	0.36
GBA-10	309.7	34.4	10	1058.2	732.4	154.2	0.42	0.36
FA-20	275.2	68.8	20	1058.2	724.3	154.2	0.42	0.36
RFA-20	275.2	68.8	20	1058.2	719.1	154.2	0.42	0.36
GBA-20	275.2	68.8	20	1058.2	733.3	154.2	0.42	0.36
FA-30	240.8	103.2	30	1058.2	714.7	154.2	0.42	0.36
RFA-30	240.8	103.2	30	1058.2	706.7	154.2	0.42	0.36
GBA-30	240.8	103.2	30	1058.2	728.1	154.2	0.42	0.36

Concrete Testing

19

- Fresh Properties
 - ▣ Slump (ASTM C143)
 - ▣ Air Content (ASTM C231)
 - ▣ Fresh Density
- Hardened Properties
 - ▣ Compressive Strength (ASTM C39)
 - At 28 and 90 days
 - ▣ Surface Resistivity (DOTD TR233)
 - At 28 and 90 days
 - ▣ Drying Shrinkage (ASTM C157)
 - ▣ Alkali Silica Reactivity (ASTM C1567)



Slump



Drying Shrinkage



Surface Resistivity



Compressive Strength



19

RESULTS





SCMs Characterization



SEM - FA




SEM - RFA



SEM - GBA




Particle Size Distribution






SCMs	Median (μm)	Mean (μm)	D10 (μm)	D90 (μm)
FA	11.5	19.2	4.4	47.0
RFA	58.8	64.5	3.3	119.3
GBA	12.5	23.2	7.3	39.2

XRF and TGA


Material	CaO	SiO ₂	Al ₂ O ₃	Fe ₂ O ₃	SO ₃	MgO	K ₂ O	Na ₂ O	Pozzolanic Component (SiO ₂ + Al ₂ O ₃ +Fe ₂ O ₃)
FA	8.4	57.2	20.2	10.2	1.2	1.6	2.7	1.1	87.6
RFA	1.8	53.4	28.0	7.7	0.1	0.99	2.2	0.3	89.1
GBA	11.0	62.0	20.8	6.9	0.5	2.8	0.9	0.3	89.7



XRD



SAI, Water Requirement, Moisture Content, and LOI



Material	Water Requirement	Moisture Content	LOI
FA	89.2%	0.40%	1.42%
RFA	95.1%	0.06%	2.95%
GBA	96.3%	0.27%	0.92%

Summary of SCMs Properties

SCM	Chemical Requirements			
	SiO ₂ +Fe ₂ O ₃ +Al ₂ O ₃ (Min. 70%)	SO ₃ (Max. 5%)	Moisture Content (Max. 3%)	LOI (Max. 6%)
FA	87.6 ✓	1.2 ✓	0.4 ✓	1.42 ✓
RFA	89.1 ✓	0.09 ✓	0.1 ✓	2.95 ✓
GBA	89.8 ✓	0.49 ✓	0.3 ✓	0.92 ✓

(✓) Met the requirement according to ASTM C618

SCM	Physical Requirements		
	Strength Activity Index (Min. 75%)		Water Requirement (Max. 105%)
	7 Days	28 Days	
FA	92.2 ✓	92.7 ✓	89.2 ✓
RFA	87.1 ✓	94.0 ✓	95.1 ✓
GBA	101.0 ✓	91.6 ✓	96.3 ✓



(✓) Met the requirement according to ASTM C618



Properties of SCMs Admixed Concrete


Fresh Properties

31




Compressive Strength

32




28 Days




90 Days

Surface Resistivity






28 Days



90 Days




Drying Shrinkage

34



Alkali Silica Reaction

35



Summary of SCMs Effect on Concrete Properties

36

Materials	Fresh Properties		Hardened Properties				Shrinkage	ASR
	Slump	Air Content	28-Day f'c	90-Day f'c	28-Day SR	90-Day SR		
FA-10	--	X	--	X	--	--	✓	✓
FA-20	✓	✓	--	X	--	✓	✓	✓
FA-30	✓	X	X	X	--	✓	✓	✓
RFA-10	X	X	--	X	--	--	✓	✓
RFA-20	X	X	X	--	--	✓	✓	✓
RFA-30	X	X	X	X	--	✓	✓	✓
GBA-10	X	X	--	--	--	✓	✓	✓
GBA-20	X	X	--	--	--	✓	✓	✓
GBA-30	X	X	--	--	--	✓	✓	✓

(✓) Impact is positive, (X) Impact is negative, (--) Impact is neutral

CONCLUSIONS

Conclusions

38

- All SCMs evaluated are promising for their use in concrete materials
 - Depending on the SCM used and cement replacement level, adjustments in the concrete mixture design and/or admixture dosage may be necessary to meet specified fresh and hardened properties
- Generally, up to 20% cement replacement with RFA and GBA can be used without compromising concrete's long-term mechanical and durability properties
- While the SCMs evaluated presented a satisfactory performance, verification should be conducted on a supplier and source basis prior to implementation in concrete mixtures

Acknowledgements

39

- Transportation Consortium of South-Central States (Tran-SET)
- Louisiana Transportation Research Center (LTRC)



Thank You!

