



New Orleans, Louisiana, USA  
March 23-24, 2024  
[www.frprcs16.com](http://www.frprcs16.com)



# Proposed Design Method for EB-FRP Ties Debond Strain Encompassing Short/Long and Thin/Thick Ties

Junrui Zhang<sup>1</sup>, Enrique del Rey Castillo<sup>1</sup>, Ravi Kanitkar<sup>2</sup>,  
Aniket D Borwankar<sup>3</sup>, and Ramprasath R<sup>4</sup>

<sup>1</sup>*The University of Auckland, New Zealand*

<sup>2</sup>*KL Structure, United States*

<sup>3</sup>*Simpson Strong-Tie, United States*

<sup>4</sup>*Virginia Tech, United States*



THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



# Unexpected strength




**Fig. 1** Bench-press by RC (*Powered by DALL·E 3*)

# Case study (*A heritage building in Auckland*)

- Weak tension capacity of concrete diaphragms



(a) Before strengthening




(b) Concrete diaphragms strengthened by FRP

**Fig. 2** State of the floor from the Project (*del Rey Castillo et al., 2019*)

# Potential variables (*1627/3162 direct tension tests from 88/117 works*)


- Parametric analysis for published data




**Fig. 3** Selected variables for published testing (*Zhang et al., 2024*)

# Potential variables (*1627/3162 direct tension tests*)


- Available Design Code/Guidelines




(a) fib Bulletin 90 design  
for IC debonding



(b) CNR DT-200 design  
for IC debonding



(c) fib Bulletin 90 design for  
end-peeling debonding




(d) CNR DT-200 design for  
end-peeling debonding

**Fig. 4** Comparison between experimental results and guide-prescribed equations (*del Rey Castillo et al., 2022*)

# Unanchored tests

**Tab. 1** Critical parameters

	Published research <i>1627</i>	Our tests <i>51</i>
<b>① Concrete strength (<math>f_c</math>)</b>	1500-10000 psi (10-90 MPa)	2500-6000 psi (17.2 to 41.4 MPa)
<b>② Bonded length (<math>l_f</math>)</b>	From 0.8" to 27" Around <b>7.8"</b> (20-700 mm, 200 mm)	<b>12" to 60"</b> (300 to 1500 mm)
<b>③ Thickness of FRP (<math>t_f</math>) (<math>k_f = nE_f t_f</math>)</b>	Around 1 or 2 layers of <b>11 oz, 0.0067"</b> (0.166-4 mm, 0.169 mm)	1 layer of 11 oz to 3 layers of 44 oz, <b>0.02 to 0.24 inches</b> (0.5-6 mm)
<b>④ Number of tests</b>	3162 tests (After cleaning 1627)	51 tests (After cleaning 48)



**Fig. 5** Testing set-up

# Debond mechanism (2500-36-2)






Fig. 6— Debonding




- Initial debonding happens
- Active bond zone progress from load end to free end, and plateau created (longer ties)
- Fully debonding of the ties

# L-D responses (36/51 unanchored tests results)



(a) 19.2 MPa, 305 mm with 1-4 layer(s)  
[2500 psi, 12 in., with 1-4 layer(s)]




(b) 36.1 MPa, 914 mm with 1-4 layer(s)  
[5000 psi, 36 in., with 1-4 layer(s)]

- Thicker ties, Stiffer, Load-carrying (/)
- Longer ties, Plateau, Load (-), Post-elastic(debonding) deformation (/)
- Concrete compressive strength (-)


**Fig. 7** Load-displacement curves (Partial)

# Contributions (1627 + 51 unanchored tests, Tyrell Gilb Research Lab, CA)




**Fig. 8** Test results of 1627+51 unanchored tested

# Failure patterns (36 unanchored tests results)




**Fig. 9—** Comparison of fractured surfaces of FRP ties considering: (a) bond lengths of FRP (Long to short), and (b) thickness of FRP (Thick to thin)

# Proposed models (*1501 +51 unanchored tests, Tyrell Gilb Research Lab, CA*)




(a) Regression algorithm



(b) Quantile-q plot (Predict)

**Fig. 10** Predictive model of unanchored tested

# Proposed models (*1501 +51 unanchored tests, Tyrell Gilb Research Lab, CA*)



**Fig. 11** Design model of unanchored tested

# Conclusion

- Thicker FRP ties influencing load-bearing capacity and longer ties showing greater post-debond deformation capacity.
- The debonding load capacity showed a certain correlation with concrete strength, but limited sensitivity to changes in bond length.
- Debond strain correlates non-linearly with FRP-to-concrete stiffness ratio, following a power relationship.

# Conclusion

- Thicker FRP ties influencing **load-bearing capacity** and **longer ties** showing greater **post-debond deformation capacity**. ( $\uparrow$ )
- The **debonding load capacity** showed a certain correlation with **concrete strength**, but limited sensitivity to changes in **bond length**. ( $-$ )
- **Debond strain** correlates **non-linearly** with FRP-to-concrete **stiffness ratio**, following a power relationship. ( $x^a$ )

# Reference

- del Rey Castillo, E. N. R. I. Q. U. E., Kanitkar, R. A. V. I., & Smith, S. T. (2019). Floor diaphragm strengthening of concrete structures with FRP. In *Proc., 2019 Concrete New Zealand Conf* (pp. 1-5).
- Zhang, J., del Rey Castillo, E., Kanitkar, R., Borwankar, A. D., & Ramprasath, R. (2024). Proposed Design Method for EB-FRP Ties Debond Strain Encompassing Short/Long and Thin/Thick Ties. *ACI-SP-360-1 Special Publication*, 360, 1-20. DOI: 10.14359/51740613
- del Rey Castillo, E., Kanitkar, R., Smith, S. T., Griffith, M. C., & Ingham, J. M. (2019). Design approach for FRP spike anchors in FRP-strengthened RC structures. *Composite Structures*, 214, 23-33.
- del Rey Castillo, E., Harries, K. A., Rogers, R., & Kanitkar, R. (2022). FRP Tension Ties: State-of-the-Art Review of Existing Design Guidance for Debonding Capacity and Applicability to Concrete Diaphragm Seismic Strengthening. *Journal of Composites for Construction*, 26(2), 04022014.
- D.K. Pudleiner, Design considerations based on size effects of anchored carbon fiber reinforced polymer (CFRP) systems, The University of Texas at Austin, USA, 2016.
- Sun, W. (2014). *Behavior of carbon fiber reinforced polymer (CFRP) anchors strengthening reinforced concrete structures* (Doctoral dissertation).
- Zhang, J., Kanitkar, R., del Rey Castillo, E., Harries, K. A., Rogers, R., & Borwankar, A. (2023, July). Bond Behaviour of FRP for Pure Axial Tension Strengthening of Concrete. In 11th International Conference on Fiber-Reinforced Polymer (FRP) Composites in Civil Engineering (CICE 2023).
- Ozbakkaloglu, T., Fang, C., & Gholampour, A. (2017). Influence of FRP anchor configuration on the behavior of FRP plates externally bonded on concrete members. *Engineering Structures*, 133, 133-150.
- Hosseini, W. M., A, B., A, S., J, L., & E, M. (2021). *Experimental investigation into strengthening of concrete diaphragm collectors using unanchored and anchored multilayer FRP reinforcement*
- Zhang, J., del Rey Castillo, E., Kanitkar, R., & D Borwankar, A. (2023, June). Behaviour of large FRP ties for seismic strengthening of concrete diaphragms. In Structural Engineering Society New Zealand (SESOC) 2023 Conference, Christchurch, New Zealand..
- Yazdani, A., Sanginabadi, K., Shahidzadeh, M.-S., Salimi, M.-R., & Shamohammadi, A. (2021). Consideration of data correlation to estimate FRP-to-concrete bond capacity models. *Construction and Building Materials*, 308, 125106.

# Acknowledgements



MINISTRY OF BUSINESS,  
INNOVATION & EMPLOYMENT  
HĪKINA WHAKATUTUKI



THE UNIVERSITY OF  
AUCKLAND  
Te Whare Wānanga o Tamaki Makaurau  
NEW ZEALAND

ENGINEERING  
DEPARTMENT OF CIVIL AND  
ENVIRONMENTAL ENGINEERING

SIMPSON

Strong-Tie

KL  
STRUCTURES



[Junrui.zhang@auckland.ac.nz](mailto:Junrui.zhang@auckland.ac.nz)  
[ajhz740@aucklanduni.ac.nz](mailto:ajhz740@aucklanduni.ac.nz)



MINISTRY OF BUSINESS,  
INNOVATION & EMPLOYMENT  
HĪKINA WHAKATUTUKI

## Thanks Q & A

SIMPSON  
Junrui Zhang  
Strong-Tie

[Junrui.zhang@auckland.ac.nz](mailto:Junrui.zhang@auckland.ac.nz)  
[ajhz740@aucklanduni.ac.nz](mailto:ajhz740@aucklanduni.ac.nz)



International Institute for  
FRP in Construction

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE

