

Completed UHPC Overlay on the Delaware Memorial Bridge: A Sustainable Solution for Prolonging the Deck Service Life

March 24, 2024

Michael McDonagh, PE, P.Eng. Shekhar Scindia, PE
Abate Tewelde, PE
Sam Boukaram, PE



THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Agenda

- Bridge Overview
- Project Need
- Replace/Rehabilitate LCCA
- Pilot Project
- Sustainability
- Full Overlay Project Execution
- Challenges and Lessons Learned
- Recommendations
- Conclusions





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE




Bridge Overview

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Bridge Overview



- 1951 Structure 1 Completed
- 1968 Structure 2 Completed
- 1969 Structure 1 Deck Replacement
- 2018 Deck Assessment and Studies (Structure 1)
- 2020 UHPC Overlay Pilot Project (Structure 1)
- 2023 Full UHPC Deck Overlay (Structure 1)


Bridge Overview (Structure 1)

- Girder spans (2 sets), Truss Spans, (2 sets) and Suspension Bridge
- 2 miles long
- 4 lanes of traffic




Bridge Overview

- 550,000 square feet of deck
- 8-inch reinf. concrete deck
- Trussed smooth transverse reinf.




Longitudinal Section
(Looking Transverse Direction)



Transverse Section
(Looking Longitudinal Direction)

7





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Project Need

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE






Project Need

- Maintenance costs were skyrocketing
- 2018 study concluded deck would need to be replaced within five to fifteen years
- Mobile Nondestructive Testing
 - Infrared Thermography (IR)
 - Ground Penetrating Radar (GPR)
 - Deck Acoustic Response (DAR)
 - High Resolution Video (HRV)
- Coring and laboratory testing


Project Need

GPR+IR
+HRV

10



DAR





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Replace/Rehabilitate LCCA

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Replace/Rehabilitate LCCA


- Replace with precast deck and stainless steel rebar for 75-year service life

OR

- Rehabilitate with partial-depth replacement “overlay”:


- Several depth options
- LMC with 12- to 25-year service life
 - (based on DRBA experience)
- UHPC with 30- to 50-year service life

13



Replace/Rehab LCCA

Year	UHPC			LMC		New Deck
	Method 1	Method 2	Method 3	Method 1	Method 2	Precast
Life Span (years)	30	50	45	12	25	75
Thickness	1.75 inch	3.75 inch	2.5 inch (plus asphalt)	1.75 inch	3.75 inch	8.0 inch
NPC compared to lowest	171%	➔ 100%	121%	255%	193%	300%



OVERLAY METHOD 2



COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Pilot Project

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Pilot Project

- Fall 2020
- 3 areas of the deck
- 25,560 SF total
- Rebar shadowing during hydrodemolition made uniform removal below rebar very labor intensive and impractical





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Full Project


THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Full Project


- 3 Phases: Fall 2022, Spring 2023, and Fall 2023
- 550,000 SF (minus pilot areas)
- Reduced UHPC thickness to 2 inches minimum (cover depth)

19



DETAIL 2

TYPICAL DECK REMOVAL AND UHPC OVERLAY



SECTION A-A



COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Sustainability

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Sustainability

- Compared 8-inch new concrete deck with plain rebar to:
 - 8.0-inch new concrete deck with galvanized rebar
 - 8.0-inch new concrete deck with stainless steel rebar
 - 1.5-inch thick LMC overlay
 - 2.0-inch thick UHPC overlay with 0.25-inch overfill
 - 1.5-inch thick UHPC overlay with 0.25-inch overfill

Sustainability

- Simplified analysis
- Considered material production only (“Cradle to gate”)
- Did **not** consider construction phase emissions:
 - No demolition activities
 - No construction activities
 - No deck forms, temporary or permanent (SIP)
 - No traffic congestion
 - No material transportation
 - No waste material disposal

Sustainability

- Only considered major carbon contributing ingredients:
 - Cement
 - Steel rebar
 - Plain, galvanized, and stainless
 - Steel fiber
 - Synthetic latex

Carbon Emissions (Day 1)

	Rel. CO ₂
Data Source	EPDs
8.0-inch Concrete Deck (uncoated reinf.)	100%
8.0-inch Concrete Deck (galvanized reinf.)	144%
8.0-inch Concrete Deck (stainless reinf.)	313%
1.5-inch LMC	22%
2.25-inch UHPC	74%
1.75-inch UHPC	58%

Carbon Emissions (Long Term)

	Rel. CO ₂ (EPD)	Service Life (years)	Rel. CO ₂ per year	Plus More...
8.0-inch Concrete Deck (uncoated reinf.)	100%	50	100%	Demolition, construction duration, traffic disruption, material transportation, bottom forms, waste disposal
8.0-inch Concrete Deck (galvanized reinf.)	144%	75	96%	
8.0-inch Concrete Deck (stainless reinf.)	313%	100	156%	
1.5-inch LMC	22%	15+	74%	Demolition/construction cycles, traffic disruption, material transport, waste disposal
2.25-inch UHPC	74%	40+	93%	Grinding
1.75-inch UHPC	58%	30+	96%	

Carbon Emissions (Long Term) – What if?

	Rel. CO ₂ (EPD)	Service Life (years)	Rel. CO ₂ per year	Plus More...
8.0-inch Concrete Deck (uncoated reinf.)	100%	50	100%	Demolition, construction duration, traffic disruption, material transportation, bottom forms, waste disposal
8.0-inch Concrete Deck (galvanized reinf.)	144%	75	96%	
8.0-inch Concrete Deck (stainless reinf.)	313%	100	156%	
1.5-inch LMC	22%	20	55%	Demolition/construction cycles, traffic disruption, material transport, waste disposal
2.25-inch UHPC	74%	50	74%	Grinding
1.75-inch UHPC	58%	50	58%	

Carbon Emissions (Long Term) – What if?

	Rel. CO ₂ (EPD)	Service Life (years)	Rel. CO ₂ per year	Plus More...
8.0-inch Concrete Deck (uncoated reinf.)	100%	50	100%	Demolition, construction duration, traffic disruption, material transportation, bottom forms, waste disposal
8.0-inch Concrete Deck (galvanized reinf.)	144%	75	96%	
8.0-inch Concrete Deck (stainless reinf.)	313%	100	156%	
1.5-inch LMC	22%	25	44%	Demolition/construction cycles, traffic disruption, material transport, waste disposal
2.25-inch UHPC	74%	80	46%	Grinding
1.75-inch UHPC	58%	80	36%	



COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Full Project

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Full Project

- Mechanical Milling 1.0 inch
- Hydrodemolition Containment



Full Project

- Hydrodemolition





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Full Project

- Hydrodemolition finish



Full Project

- Mixing Equipment



Full Project

- Transport Equipment





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE: A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Full Project

- UHPC Placement
- Only 2 lanes closed



Full Project

- Curing without Plastic Sheetting



Full Project

- Grinding and Grooving





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Full Project

- Finished Surface





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE





Challenges and Lessons Learned

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Challenges and Lessons Learned

- Challenge to fully contain hydrodemolition slurry with open gutters
- Containment system required multiple layers of protection
- Spilled slurry should be washed off structure immediately



Challenges and Lessons Learned

- Deck grinding
- Quality grinding is important for ride quality



Challenges and Lessons Learned

- Air holes in deck surface
 - Many widespread surface holes on some placements
 - Very few surface holes on other placements
 - About 50% > 5/8-inch deep
 - A small minority of holes 1.5 inch to 2 inches deep
 - Holes were opened up, if necessary, and filled with UHPC slurry with no fiber

Challenges and Lessons Learned

- Air holes in deck surface
 - Many were very small at the surface and easy to overlook.
 - Very small holes were often wider below the surface

44



Challenges and Lessons Learned

- Fiber balling due to never-before-used automated mixing equipment.
Addressed by:
 - Slowing down mixing process
 - Adjustments to mixing equipment
 - Removal of fiber balls from fresh mix
 - Areas with many fiber balls on finished surface had surface removed and replaced with new UHPC
 - Isolated fiber balls were cleaned out and filled with UHPC slurry





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Challenges and Lessons Learned Fire Damage

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



LIVE May 30, 2023



BREAKING NEWS

NORTHBOUND LANES OF DELAWARE MEMORIAL BRIDGE CLOSED



COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Fire Damage



Fire Damage

- Multiple spalls \approx 0.75-inch deep
- No evidence of explosive spalling other than very small bits of fiber and UHPC on top of parapet.



Fire Damage Emergency Repair

- Schibeci grinder used to remove area to 1-inch depth
- Left lots of exposed fiber on bottom surface



Fire Damage Emergency Repair

- Bicycle screed used to place UHPC
- No overfill

Fire Damage Emergency Repair

- 14 months later



Challenges and Lessons Learned UHPC Replacement (Yes you can!)



UHPC Replacement

- Called for 1 inch removal and replacement
- UHPC was one year old
- UHPC surface was removed by hydrodemolition



UHPC Replacement

- Hydrodemolition left exposed fiber



UHPC Replacement

- Hydrodemolition removed all UHPC in some areas
- No blow throughs




UHPC Replacement

- Local area UHPC removed with hydrodemo hand lance
- Steps were created at edges of repair areas
- All original UHPC was removed in significant portions of repair areas




UHPC Replacement

- 
- A photograph showing construction workers on a bridge deck. Several workers in high-visibility vests and hard hats are operating a large, red, portable truss screed machine. The machine is used for applying and leveling UHPC (Ultra-High Performance Concrete) for deck repairs. The bridge structure, including its cables and towers, is visible in the background. The scene is set during the day, with a clear sky.
- UHPC for full deck panel repairs was placed using same methods used for main overlay
 - UHPC for local area repairs was placed using portable truss screed
 - All repairs were overfilled, grinded, and grooved



UHPC Replacement

- Completed local area repair





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Challenges and Lessons Learned Successes

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Challenges and Lessons Learned

- Successful placement adjacent to live traffic
- Successful placement in downhill direction



Challenges and Lessons Learned

- UHPC overlays can be successfully installed on major bridges





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Recommendations

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Recommendations

- **Design**
 - Limit removal/replacement thickness to the concrete cover
 - UHPC will waterproof the deck which should stop corrosion, regardless of chloride levels
 - Reduces cost and maximizes sustainability
- **Demolition**
 - Mill as much as possible to minimize hydrodemolition
 - Ensure tight wastewater containment and wash off spills ASAP
 - Explore alternatives to hydrodemolition such as shotblasting

Recommendations

- **UHPC Mockup**
 - Perform full-size mockup with actual production equipment
 - Use mockup substrate with roughness to mimic bridge deck prep
 - Grind the cured mockup to expose any fiber balls and air holes
 - Repeat, if necessary, until no fiber balls and minimal air holes
- **QC Specifications**
 - Include spec language to ensure surface defects are repaired.
 - Include ride quality criteria if not already part of standard specs.



COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Conclusions

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Conclusions

- Installation of a 2-inch-thick UHPC overlay on the entire deck of the Delaware Memorial Bridge first structure was a success
- First UHPC overlay on an entire long-span bridge in North America
- Largest UHPC overlay in North America by surface area and by volume
- Methods for temporary and permanent repairs of UHPC overlay were successful
- UHPC is expected to extend the service life of the deck by 40 years
- Lifecycle cost analysis indicates that the UHPC overlay is the most cost-effective option for deck rehabilitation/replacement
- Simplified calculation suggests that a UHPC overlay is the most sustainable option for deck rehabilitation/replacement



Thank you

Michael McDonagh, PE, P.Eng.
Abate Tewelde, PE
Sam Boukaram, PE

Shekhar Scindia, PE

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



Appendix

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE



UHPC Overlay Service Life Basis

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



UHPC Overlay Service Life Basis

- 21-year long studies on Treat Island, Maine by Dr. Michael Thomas
 - Chloride penetration after 21 years < 0.25 inch
 - Time to initiate rebar corrosion with 2-inch cover ≥ 400 years



UHPC Overlay Service Life Basis

- Morge River Bridge Rehabilitation, Switzerland
 - UHPC placed in 2004
 - Deck soffit left unrepaired
 - No soffit deterioration or water infiltration since then

72





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE





Challenges and Lessons Learned

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Challenges and Lessons Learned

- Air holes in deck surface
 - Indicates less than 100% consolidation
 - Not isolated to this project
 - Industry needs to improve understanding and techniques



Challenges and Lessons Learned

- UHPC overlay surface can be removed and replaced
 - Fire damage
 - Fiber balls
 - Removed 1-inch+ with methods that leave exposed fiber
 - Steps at construction joints





COMPLETED UHPC OVERLAY ON THE DELAWARE MEMORIAL BRIDGE:
A SUSTAINABLE SOLUTION FOR PROLONGING THE DECK SERVICE LIFE




Sustainability

THE WORLD'S GATHERING PLACE FOR ADVANCING CONCRETE



Sustainability



Carbon Emissions

	Rel. CO ₂ V1	Rel. CO ₂ V2	Rel. CO ₂ V3
Data Source	Various	Winnipeg	EPDs
8.0-inch Concrete Deck (uncoated reinf.)	100%	100%	100%
8.0-inch Concrete Deck (galvanized reinf.)	119%	117%	144%
8.0-inch Concrete Deck (stainless reinf.)	251%	235%	313%
1.5-inch LMC	16%	14%	22%
2.25-inch UHPC	36%	38%	74%
1.75-inch UHPC	28%	30%	58%