



U.S. Department of Transportation
Federal Highway Administration

Turner-Fairbank
Highway Research Center

Ultra-High Performance Concrete (UHPC) Bridge Deck Overlays as a Corrosion Mitigation Strategy to Ensure Longer Service Life

Scott Muzenski, Ph.D, P. E.
Genex Systems

Naveen Saladi
Genex Systems

Benjamin Graybeal, Ph.D, P. E.
Federal Highway Administration (FHWA)

*American Concrete Institute - Spring Convention
March 24, 2024*

Source: FHWA.



Disclaimer

This presentation was created and is being co-presented by both FHWA and contractors. The views and opinions expressed in this presentation are the presenter's and do not necessarily reflect those of FHWA or the U.S. Department of Transportation (USDOT). The contents do not necessarily reflect the official policy of the USDOT.

The U.S. Government does not endorse products or manufacturers. Trademarks or manufacturers' names appear in this presentation only because they are considered essential to the objective of the presentation. They are included for informational purposes only and are not intended to reflect a preference, approval, or endorsement of any one product or entity.




UHPC Overlays as a Bridge Preservation Method



Source: FHWA.



Source: FHWA.




Source: FHWA.

UHPC overlay properties (FHWA 2019):


- ▶ Cement-based composite with an optimized gradation of granular constituents.
 - ▷ High cementitious contents.
 - ▷ Water-to-cementitious materials ratio <0.25 .
 - ▷ Increased admixture dosages.
 - ▷ Fiber reinforcement dosage of 3.25 percent.
- ▶ High compressive strength ($>18,000$ psi).
- ▶ High sustained tensile strength (>720 psi).
- ▶ Thixotropic in nature.
- ▶ Reduced overlay thickness compared to conventional overlays.

Approach to Sustainability and Cost Analysis

Affected by the Performance of the Material



Source: FHWA (2020).



Source: FHWA.

Previous Research on UHPC LCA/LCCA*

Material Constituents	Material Performance	LCA/LCCA Outcomes
High environmental impact and high materials costs	Improved durability and mechanical performance	Potential reduction in environmental impact and lifecycle costs when service life is considered
High cementitious content	Longer service life for critical durability	
Steel fibers	Optimized structure geometry from improved mechanical performance	
High-quality filler material	Less maintenance costs	
High admixture dosage		



Image Source: FHWA (Haber et al. 2023).

*See Harvey et al. (2020) and Haber et al. (2023).

UHPC Bridge Deck Overlay Performance

UHPC overlays are used to extend the lifespan of a bridge deck; however, a long service life for the overlay must still be ensured:

- ▶ Part I: Structural Performance of Joints in UHPC Bridge Deck Overlays to Ensure Longer Service Life.
- ▶ Part II: UHPC Bridge Deck Overlays as a Corrosion Mitigation Strategy to Ensure Longer Service Life.



Source: FHWA.





Source: FHWA

Part I: Structural Performance of Joints in UHPC Bridge Deck Overlays to Ensure Longer Service Life



U.S. Department of Transportation
Federal Highway Administration

Turner-Fairbank
Highway Research Center

Cold Joints in Overlays


UHPC overlays are commonly constructed in phases:

- ▶ Cold joint occurs between adjacent phases.
- ▶ Cold joints may allow water and chlorides to permeate the substrate deck concrete.
- ▶ Cold joints may be the weak link from a structural standpoint.



Schematic

Source: FHWA.



Source: FHWA.

Cyclic Structural Testing

- ▶ Negative moment bending (UHPC is in tension).
- ▶ Conventional concrete substrate precycled to represent mature deck.
- ▶ Roughened surface produced by hydro-demolition.
- ▶ Specimens cycled at incrementally increasing moments corresponding to the UHPC's cracking stress and localization strain.



Source: FHWA.





Source: FHWA.

Cold Joint Detailing (1 of 3)

Three scenarios were considered for structural testing:


- ▶ **Reference (no cold joint).**
- ▶ Cold joint with bonding agent.
- ▶ Stepped cold joint.



Cold Joint Detailing (2 of 3)

Three scenarios were considered for structural testing:

- ▶ Reference (no cold joint).
- ▶ **Cold joint with bonding agent.**
- ▶ Stepped cold joint.



Source: FHWA.





Source: FHWA.

Cold Joint Detailing (3 of 3)


Three scenarios were considered for structural testing:

- ▶ Reference (no cold joint).
- ▶ Cold joint with bonding agent.
- ▶ **Stepped cold joint.**



Flexural Stiffness During Cycling

- ▶ Reference sample:
 - ▷ Flexural stiffness was maintained below the tensile cracking moment.
 - ▷ Some reduction in stiffness was observed when cycled beyond the tensile cracking limit.
- ▶ Cold joint with bonding agent:
 - ▷ Flexural stiffness began to reduce during cycling.
 - ▷ Joint opening continued to expand during cycling.
- ▶ Stepped cold joint:
 - ▷ Flexural stiffness was maintained throughout cycling.
 - ▷ Joint width did not appear to expand.




Source: FHWA.

Crack/Joint Opening During Cycling

Reference




Bonding Agent



Stepped Joint



All images source: FHWA.



Source: FHWA.

Summary

- ▶ Cyclic loading when a UHPC overlay is in tension (beyond the UHPC cracking limit but before the localization limit) may result in reduced flexural stiffness and an increased crack opening.
- ▶ Cold joints created with a bonding agent at the interface were unable to sustain flexural stiffness at higher flexural moments and extended cyclic testing.
- ▶ Stepped cold joints were able to sustain flexural stiffness and maintain a low joint opening throughout cyclic testing.





© 2015 USchools / iStock.

Part II: UHPC Bridge Deck Overlays as a Corrosion Mitigation Strategy to Ensure Longer Service Life



U.S. Department of Transportation
Federal Highway Administration

Turner-Fairbank
Highway Research Center

Statements and Objective

- ▶ **Statements:**
 - ▷ Corrosion has become one of the leading contributors to bridge deck deterioration.
 - ▷ Corrosion of reinforcing steel can result in a reduced deck capacity.
 - ▷ Effective corrosion mitigation strategies are necessary to ensure longer service life of bridge decks.
 - ▷ Bridge deck overlays and corrosion mitigation chemicals (CMC) are of interest in this study.
- ▶ **Objective:** Evaluate the performance of the UHPC overlay by itself or in conjunction with different corrosion mitigation strategies.



Materials

- ▶ Substrate concrete—A4 concrete (VDOT 2016).
- ▶ Steel—ASTM A615 grade 60 U.S. No. 4 (ASTM 2022a).
- ▶ Overlays:
 - ▷ Commercially available UHPC overlay (**1.5 inches thick**).
 - ▷ LMC overlay (**2 inches thick**).
- ▶ CMC:
 - ▷ Soy-based sealer (S-1).
 - ▷ Amino alcohol-based corrosion inhibitor (CI-1).
 - ▷ Hybrid silane-based sealer and corrosion inhibitor (SCI-1).
 - ▷ Hybrid silane-based sealer and corrosion inhibitor (SCI-2).




Specimen Preparation and Test Matrix

▶ Corrosion performance:

- ▷ Corrosion potential (C876 (ASTM 2022b)).
- ▷ Cyclic polarization (G61 (ASTM 2018)).

▶ Bond performance:
Direct tension bond testing (C1583 (ASTM 2020)).

(FHWA-HRT-22-087)




Source: FHWA.

Results—Corrosion Potential


According to ASTM C876, the relationship between potential measurements and corrosion probability is as follows (ASTM 2022b):

Measured Potential (mV/CSE)	Probability of Nonnegligible Steel Corrosion Activity (percent)
> -200	<10
-200 to -350	Uncertain
< -350	>90




Source: FHWA.

Results—Cyclic Polarization



Source: FHWA.

Results—Direct Tension Bond Test



Source: FHWA.

Conclusions (1 of 2)

A commercially available UHPC overlay material used in combination with common CMCs was compared to a conventional LMC overlay in terms of corrosion propensity over time:

- ▶ Use of overlays by themselves or in conjunction with CMCs reduced corrosion propensity.
- ▶ LMC and UHPC overlays reduced corrosion rates by 20 and 50 percent, respectively, compared to no overlay.



Conclusions (2 of 2)

- ▶ Despite the reduced overlay thickness, lower corrosion rates were observed in UHPCs compared to LMC, potentially due to the lower permeability of UHPCs.
- ▶ Use of CMCs in combination with UHPC overlay reduced corrosion rates further. However, the presence of CMCs along the overlay-to-concrete interface had a clear, negative effect on the long-term bond performance.



References

- ▶ ASTM. 2018. *Standard Test Method for Conducting Potentiodynamic Polarization Measurements for Localized Corrosion Susceptibility of Iron-, Nickel-, or Cobalt-Based Alloys*. ASTM G61. West Conshohocken, PA: ASTM International.
- ▶ ASTM. 2020. *Standard Test Method for Tensile Strength of Concrete Surfaces and the Bond Strength or Tensile Strength of Concrete Repair and Overlay Materials by Direction Tension (Pull-off Method)*. ASTM C1583. West Conshohocken, PA: ASTM International.
- ▶ VDOT. 2016. *Road and Bridge Specifications*. Richmond, VA: VDOT. https://www.vdot.virginia.gov/media/vdotvirginiagov/doing-business/technical-guidance-and-support/technical-guidance-documents/construction/migrated-acc/VDOT2016_2Specs_acc071522.pdf, last accessed January 26, 2024.
- ▶ ASTM. 2022a. *Standard Specification for Deformed and Plain Carbon-Steel Bars for Concrete Reinforcement*. ASTM A615. West Conshohocken, PA: ASTM International.
- ▶ ASTM. 2022b. *Standard Test Method for Corrosion Potentials of Uncoated Reinforcing Steel in Concrete*. ASTM C876. West Conshohocken, PA: ASTM International.
- ▶ FHWA. 2019. *Design and Construction of Field-Cast UHPC Connections*. Publication No. FHWA-HRT-19-011. Washington, DC: FHWA.
- ▶ FHWA. 2020. *Data Needs for Pavement LCA: What Agencies Need to Know*. Publication No. FHWA-HIF-109-101. Washington, DC: FHWA. <https://www.fhwa.dot.gov/pavement/sustainability/pubs/hif19101.pdf>, last accessed February 1, 2024.
- ▶ Haber, Z. B., M. McDonagh, A. Foden, and S. Sadasivam. 2023. *Ultra-High Performance Concrete (UHPC) Overlays: An Example of Lifecycle Cost Analysis*. Publication No. FHWA-HRT-23-012. Washington, DC: FHWA.
- ▶ Harvey, J., I. L. Al-Qadi, H. Ozer, and G. Flintsch (Eds.). 2020. *Pavement, Roadway, and Bridge Life Cycle Assessment 2020*. London, UK: Taylor & Francis Group.
- ▶ FHWA. 2022. *Techniques to Inhibit Corrosion in Bridge Deck Reinforcement Prior to Overlay Installation*. Publication No. FHWA-HRT-22-087. Washington, DC: FHWA.



Questions?



Contacts

Naveen Saladi

Concrete Materials Research Engineer,
Genex Systems

naveen.saladi.ctr@dot.gov

Scott Muzenski

Concrete Materials Research Engineer,
Genex Systems

scott.muzenski.ctr@dot.gov

Ben Graybeal, Ph.D., P.E.

Team Leader - Bridge Engineering Research
Federal Highway Administration

benjamin.graybeal@dot.gov



U.S. Department of Transportation
Federal Highway Administration

Turner-Fairbank
Highway Research Center

Abbreviations

ASTM	American Society for Testing and Materials
CI-1	corrosion inhibitor-1
CMC	corrosion mitigation chemicals
CSE	copper sulfate electrode
FHWA	Federal Highway Administration
LCA	lifecycle assessment
LCCA	lifecycle cost assessment
LMC	latex modified concrete
LVDT	linear variable differential transformer
mpy	mils per year
S-1	sealer-1
SCI-1 and SCI-2	sealer and corrosion inhibitor-1 and -2
UHPC	ultra-high performance concrete
VDOT	Virginia Department of Transportation

